

Intel® Embedded Media and Graphics Driver Feature Matrix Version 1.16

Ideal for systems based on the Intel® Atom™ processor E6xx series (E620/E620T/E640/E640T/E660/E660T/E680/E680T) which integrates the processor core, graphics, video encode/decode, memory, and display controllers in one package. Also validated for platforms based on the Intel® Atom™ processor Z5xx series with the Intel® System Controller Hub US15W, US15WP and US15WPT.

This driver is enhanced over previous embedded graphics drivers from Intel, providing higher performance, a rich feature set, and improved usability. For detailed product information, please visit edc.intel.com/software/downloads/EMGD.

Intel® Embedded Media and Graphics Driver Features	Intel® Atom™ Processor E6xx Series	Intel® System Controller Hub US15W/US15WP/US15WPT
Driver		
Cross-platform, cross-OS Configuration EDitor (CED) utility for creation of driver packages (Windows® 32-bit and 64-bit environments supported)	x	x
Installer/uninstaller (Microsoft Windows® only), RPM method supported for Linux®	x	x
CED Lite, provided as a browser-based GUI utility, can be used on Windows®- or Linux®-based systems	x	
Runtime GUI (Windows and Linux® only)	x	x
Runtime control API on internal LVDS and external encoders	x	x
Second overlay	x	x
Rendered scaling and centering	x	x
Multi-GPU, Multi-monitor (PCI- and PCI Express®-based, as primary or secondary, concurrent with integrated graphics) for Microsoft Windows® XP	x	
Enhanced clone mode support for use with different-sized displays	x	x
Multi-GPU, Multi-Monitor (PCI Express®-based as secondary concurrent with integrated graphics as primary) for Microsoft Windows® 7 and Windows® Embedded Standard 7	x	
Hardware Video Decode Acceleration		
MPEG-2 (MPlayer/FFMPEG), MPEG-4, H.264, and VC-1 via VA-API (Linux with MPlayer/FFMPEG and GStreamer)	x	x
MPEG-2, H.264, VC-1 supported via DXVA (Windows)	x	x
MPEG-2, MPEG-4, H.264 formats supported in Microsoft Windows® CE 6.0 via EMGD v1.5.3	x	x
MPEG-2, H.264 AVC, VC-1 and WMV9 via DXVA 2.0 (Windows® 7/Windows® Embedded Standard 7)	x	x
Adobe Flash® 10.1 video decode support with a third-party plug-in (Linux only)	x	x
MPEG-4, H.264 AVC, VC-1, and H.263 formats supported via OpenMAX® in Android® via EMGD v1.14	x	
Anti-Aliasing	x	x
Certified Output Protection Protocol (COPP) support on Microsoft Windows® XP	x	x
Hardware Video Encode Acceleration		
H.264/MPEG-4 (Linux)	x	
H.264 (Windows® 7/Windows® Embedded Standard 7)	x	
Configurability		
Ability to configure port names used in the runtime GUI	x	x
Ability to change resolution/refresh rates for clone displays in the runtime GUI	x	x
Advanced Extended Display Identification Data (EDID) configuration	x	x
Full ACPI support on Windows® (not available on Windows® CE) and Linux	x	x
Display rotation and flip configuration based on DID physical orientation information	x	x
Display discovery and initialization (driver only)	x	x
Dual digital display outputs through single sDVO device (e.g., Chrontel CH7319/7320*)	x	x
Dynamic port driver	x	x
Ability to set port as inactive when not in single mode	x	x
Universal .inf for multiple platform configuration (Windows only)	x	x
Dynamic mode support using EDID information (dynamically adds new timing sets fully described in EDID)	x	x
Multi-refresh, multi-resolution support (driver does not assume fixed resolution or timings on digital display)	x	x
Rotation and inverted display	x	x
Allows manual specification of display timing sets	x	x
EDID-less (non-EDID compliant) display support	x	x
Dual independent display [Microsoft Extended Desktop, * Linux Xinerama (depends on distro support), and dual independent head (DVI-H)]	x	x
Clone dual display support	x	x
Hot-plug support of displays on Windows® 7 Professional, Windows® 7 Ultimate and Windows® Embedded Standard 7	x	
Ability to swap primary display of clone or extended mode during runtime (Windows XP only)	x	

Intel® Embedded Media and Graphics Driver Features	Intel® Atom™ Processor E6xx Series	Intel® System Controller Hub US15W/US15WP/US15WPT
Display Output		
Internal LVDS	X	X
Silicon Image sDVO devices: Si1 1362* and Si1 1364* (DVI)	X	X
Chrontel sDVO: CH7307* (DVI), CH7308* (LVDS), CH7315* (HDMI), CH7317B* (HDTV/VGA RGB), CH7022* (VGA), CH7319* (DVI with HDCP), CH7320* (DVI)	X	X
Chrontel CH7036* support for conversion from LVDS to HDMI/DVI and VGA	X	X
Chrontel CH7022* TV-Out support with YPbPr on Linux	X	
Lapis Semiconductor ML7213*-sDVO	X	
UEFI Video Driver		
Normal and fast boot	X	X
Intel® Boot Loader Development Kit (BLDK) for Linux and Windows CE (depends on capability availability)	X	X
XSe* Fast Boot Loader support for Linux	X	
EFI splash screen file size up to 500 KB	X	
VBIOS		
Embedded VBIOS support (e.g., LVDS brightness control at boot)	X	X
Display discovery and initialization	X	X
Full VESA mode support/VESA modes 115h and 118h support	X	X
POST to internal LVDS or sDVO	X	X
Full VGA modes support	X	X
EDID-less (non-EDID compliant) display support	X	X
Video BIOS multi-configuration support of up to 64K on Windows* XP, Windows* 7 and Linux	X	
Video BIOS multi-configuration support of only 127K on Windows* XP, Windows* 7, and Linux	X	
OSs and APIs		
Runtime operation API	X	X
Support for default VGA modes	X	X
Port driver software development kit (Windows and Linux)	X	X
DOS* support (IBM PC 2000,* MS 6.22)	X	X
Microsoft		
Windows* XP (SP3), Windows* XP Embedded Standard 2009, Windows* Embedded for Point of Service	X	X
DirectDraw* (DirectX* 9.0c, DirectX 8.1, DirectX 3)	X	X
Direct3D* (DirectX 9.0c, DirectX 8.1)	X	X
DirectX* Texture Compression (DXTC)	X	X
Microsoft DirectX Runtime API (DirectX 8.1 SDK samples in windowed and full-screen mode)	X	X
Support in English language mode for multi-language OS environment, i.e., Japanese, Traditional Chinese, Korean	X	X
Windows* Embedded CE 6.0 R3* via EMGD v1.5.3 on E6xx B0	X	
Windows* Embedded Compact 7.0 via EMGD v1.16 on E6xx B1	X	
DirectDraw	X	
Direct3D Mobile (excluding vertex processing emulation)	X	
Vertical extended display support/rotation	X	
Framebuffer overlay blending; Framebuffer direct access during runtime for display customized image	X	
OpenGL* 2.0, OpenGL ES 1.1, OpenGL ES 2.0	X	
Windows* 7 Professional, Windows* 7 Ultimate and Windows* Embedded Standard 7 (does not support Intel® Atom™ processor E620/E620T [0.6 GHz] due to minimum system requirements of 1.0 GHz 32-bit [x86] processor)	X	X
2D GDI Hardware Acceleration	X	X
Direct3D (DirectX 9.0c/9.0L)	X	X
OpenGL 2.0 support	X	X
Linux		
OpenGL 2.1	X	X
OpenGL ES 1.1 and 2.0 support (API added for PVRTC compressed texture format)	X	X
OpenGL 1.4, OpenGL 1.5	X	X
OpenVG 1.1 support	X	X
Framebuffer Overlay Blending	X	X
User interface ColorKey support via XV	X	X
Video decode texture streaming	X	
API for overlay plane selection, sharing of EGL surfaces between applications with MSAA, and freeze/resume of frame buffer rendering	X	
Dual independent head-to-clone/reverse-clone mode runtime switching, direct DMA to overlay and frame buffer functionality for external video inputs, and vertical extended mode support on MeeGo* 1.2	X	
Timesys Fedora* Remix v14 (Timesys kernel 2.6.35, X Server 1.9, Mesa 7.9)	X	X
MeeGo* 1.2 IVI Linux (kernel 2.6.37 and 2.6.39, X Server 1.9, Mesa 7.9)	X	X
Android* via EMGD 1.14		
Android Composition Manager, SurfaceFlinger*, StageFright support	X	
OpenGL ES 1.1 and 2.0 support	X	
Overlay support, video decode blend and texture streaming, and video encode using a USB camera	X	
Android 2.3.7 (Gingerbread kernel 2.6.39)	X	

To see which embedded Intel® architecture processors are validated with each Intel® chipset, visit intel.com/intelligentsystems.

¹Windows Embedded CE* R2 on Intel® System Controller Hub US15W/US15WP/US15WPT is supported by the IEGD (edc.intel.com/software/downloads/IEGD).

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT, EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS. INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

Copyright © 2012 Intel Corporation. All rights reserved. Intel, the Intel logo, and Atom are trademarks of Intel Corporation in the U.S. and other countries.

*Other names and brands may be claimed as the property of others.

Printed in USA

1112/KSC/OCG/XX/PDF

✿ Please Recycle

324002-008US

