



DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	10.0	+3.0/-3.0	PLATED	154
•	36.0	+3.0/-3.0	PLATED	17
•	37.008	+3.0/-3.0	PLATED	12
•	41.0	+3.0/-3.0	PLATED	10
▪	92.913	+3.0/-3.0	PLATED	4
▪	110.0	+3.0/-3.0	PLATED	6
•	155.12	+3.0/-3.0	PLATED	2
Ⓚ	128.0	+2.0/-2.0	NON-PLATED	4



- NOTES:
- 1. THIS BOARD IS RoHS COMPLIANT.
  - 2. PRINTED WIRING BOARD DESIGN AND ACCEPTANCE CRITERIA SHALL BE IAW WITH THE REQUIREMENTS OF IPC-D-275 AND IPC-A-600.
  - 3. MATERIAL: FR4 (ROHS COMPLAINT) , 1 OZ COPPER.
  - 4. APPLY SOLDER MASK, BOTH SIDES OVER BARE COPPER IAW IPC-SM-840. CLASS 2 (LPI) (GREEN MASK).
  - 5. ALL PATTERNS ARE VIEWED FROM THE PRIMARY SIDE LOOKING THROUGH THE BOARD.
  - 6. UNLESS OTHERWISE SPECIFIED ALL HOLE DIAMETERS ARE AFTER PLATING.
  - 7. APPLY SILKSCREEN USING WHITE NON-CONDUCTIVE EPOXY BASED INK.
  - 8. PWB MUST BE 100% ELECTRICALLY TESTED FOR SHORTS AND CONTINUITY. USE NETLIST PROVIDED EVB-ER21200I\_IPC356.IPC IAW IPC-D-356.
  - 9. MARK DATE CODE AND MANUFACTURES IDENTIFICATION ON SOLDER SIDE PER IPC-6011 AND IPC-6012.
  - 10. TOLERANCE ON ALL DRILL HOLES SHALL BE IAW IPC-D-2221 & 2222 UNLESS OTHERWISE SPECIFIED.

Drawn By:	Date Drawn:	Engineer:		
Released By:	Date Released:	EVB-ER21200I		
DIMENSION ARE IN INCHES		Fabrication Drawing		
	DATE:	MASK#	DWG NO.	REV.
		N/A	09346	A
FILENAME:				SHEET
				1 of 1