



82546 EB/GB Gigabit Ethernet Controller Thermal Properties with External Heat Sink

Application Note (AP-458)

Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life saving, or life sustaining applications.

Intel may make changes to specifications and product descriptions at any time, without notice.

The 82545EM, 82545GM, 82546EB and 82546GB may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

This document and the software described in it are furnished under license and may only be used or copied in accordance with the terms of the license. The information in this document is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Intel Corporation. Intel Corporation assumes no responsibility or liability for any errors or inaccuracies that may appear in this document or any software that may be provided in association with this document. Except as permitted by such license, no part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means without the express written consent of Intel Corporation.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order.

Copies of documents which have an ordering number and are referenced in this document or other Intel literature may be obtained by calling 1-800-548-4725 or by visiting Intel's website at <http://www.intel.com>.

Copyright © 2003 Intel Corporation.

* Third party Other names and brands may be claimed as the property of others.



Revision History

Date	Revision	Description
Dec 2003	0.5	Initial Releasez



Note: This page is intentionally left blank.



Contents

1.0	Introduction	1
2.0	Result Summaries	1
3.0	Conclusion	2
4.0	Methodology	2
4.1	Junction Temperature Measurement.....	2
4.2	Test Condition.....	2
5.0	Package Information	3
5.1	Package Description	3
5.2	Passive Heat Sink Description	3
5.3	Test Board Description	4
5.4	Assembly Material	4
A	Terminology	5



Note: This page is intentionally left blank.

1.0 Introduction

This report presents the thermal measurement results of PBGA 364 in terms of junction-to-ambient thermal resistance (θ_{JA}), junction-to-case thermal resistance (θ_{JC}). The measurement included the component and the HS evaluation.

2.0 Result Summaries




Figure 1. Thermal Performance of PBGA 364 under Forced Convection




Figure 2. Thermal Resistance of PBGA364 under Natural Convection

3.0 Conclusion

From the measurement results, we can obtain the q_{JA} . Assuming applicable ambient temperature of 65°C and maximum junction temperature of 125°C, we can predict the power dissipation capability of this package as below table.

Air Flow (LFPM)		0	100	200	300
Power Dissipation (watt)	STD	3.35	4.13	4.44	4.72
	with Passive HS	4.51	6.18	7.5	8.69

4.0 Methodology

4.1 Junction Temperature Measurement

In this measurement the packages were built using standard practice with 300 mil thermal die.

4.2 Test Condition

Packages were mounted on 4-layer test boards and are measured for thermal resistance under forced convection. The tests were conducted inside a closed-loop wind tunnel system which controls temperature from 18°C to 65°C and wind speed from less than 0 m/s to 5 m/s. The measured temperature data will be taken by a data acquisition system. In forced convection, airflow is applied from 0 m/s to 3 m/s which the heating power for packages is fixed at 3.5 W and the surrounding temperature is 22 ± 1°C. Samples are measured and the average thermal resistances are calculated. The test conditions summaries are shown below.

Condition	Setting
Heating Power	3.5 watts
Test Board	4-layer
Control Condition	Air Speed = 0, 1, 2, 3 m/s
Ambient Temp.	22±1°C
Test Samples	3 pieces

5.0 Package Information

5.1 Package Description

Type	364-Pin PBGA
Drawing NO	I-1244 (4L)
Dimension (L x W)	21 x 21 mm
Package Thickness	2.23 mm (including solder ball)
Chip Size	7.77 x7.77 mm (300 x 300 mil)
Die Thickness	0.3048 mm
Ball pitch / Ball Diameter	1.0 mm / 0.6 mm
Number of Cu Layer	4-layer (2oz)
Thermal Ball	40
Thermal Via	51

5.2 Passive Heat Sink Description

Type	AAVID 335314
Dimension	<p>The drawing shows a square heat sink with a side length of 1.060 mm (26.92 mil). The side view shows a height of 1.06 mm (26.92 mil) and a base width of 0.45 mm (11.43 mil). The top surface has a width of 0.13 mm (3.30 mil) at the top edge.</p>

5.3 Test Board Description

Material	FR-4
Dimension (L x W)	4" x 4.5"
Thickness	1.6 mm
Number of Cu Layer	4-layer (2S2P) (Inner layer Cu coverage 40%)
Part Number	BA-20-10-04

5.4 Assembly Material

Component	Material	Thermal Conductivity (w/m-k)
Die	Silicon	147
Substrate	BT	0.2
Silver Paste	8360	2.9
Mold Compound	SMT-B-1	0.71
PCB	FR4	0.2
	Cu	396
Solder Balls	63Sn/37Pb	50
Drop-in H/S	Cu	396

Appendix A Terminology

The major thermal dissipation paths can be illustrated as following

T_J : the maximum junction temperature;

T_A : the ambient or environment temperature;


T_C : the center of top compound surface temperature;

P : total input power

Junction to ambient thermal resistance, θ_{JA} , defined as:

1. Junction to ambient thermal resistance, θ_{JA} , defined as:

$$\theta_{JA} = \frac{T_J - T_A}{P}; \quad (1)$$




Thermal Dissipation of BGA

2. Junction to case thermal resistance, θ_{JC} , defined as:

$$\theta_{JC} = \frac{T_J - T_C}{P}; \quad (1)$$

Attach a block with constant temperature onto package





Note: This page is intentionally left blank.