

# Intel® Desktop Compatibility Tool

Found 16 Compatible Processor(s) for Board D5400XS

## Quad-Core Intel® Xeon® X5482 | Frequency: 3.20 GHz

[More Information](#)

Cache	Graphics	Max TDP
12 MB	No	150
Spec #	Min. BIOS	AA Rev(s)
SLANZ	1148	D94664-402
SLANZ	1148	D94664-403
SLANZ	1148	D94664-500
SLANZ	1148	D94664-501
SLANZ	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® X5472 | Frequency: 3.00 GHz

[More Information](#)

Cache	Graphics	Max TDP
12 MB	No	120
Spec #	Min. BIOS	AA Rev(s)
SLASA	1148	D94664-402
SLASA	1148	D94664-403
SLASA	1148	D94664-500
SLASA	1148	D94664-501
SLASA	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® X5460 | Frequency: 3.16 GHz

[More Information](#)

Cache	Graphics	Max TDP
12 MB	No	120
Spec #	Min. BIOS	AA Rev(s)
SLANP	1148	D94664-402
SLANP	1148	D94664-403
SLANP	1148	D94664-500

SLANP	1148	D94664-501
SLANP	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® X5450 | Frequency: 3.00 GHz

[More Information](#)

Cache	Graphics	Max TDP
12 MB	No	120
Spec #	Min. BIOS	AA Rev(s)
SLASB	1148	D94664-402
SLASB	1148	D94664-403
SLASB	1148	D94664-500
SLASB	1148	D94664-501
SLASB	1148	D94664-502

Add-in graphics card required

## Dual-Core Intel® Xeon® X5272 | Frequency: 3.40 GHz

[More Information](#)

Cache	Graphics	Max TDP
6 MB	No	80
Spec #	Min. BIOS	AA Rev(s)
SLANH	1148	D94664-402
SLANH	1148	D94664-403
SLANH	1148	D94664-500

Add-in graphics card required

## Dual-Core Intel® Xeon® X5260 | Frequency: 3.33 GHz

[More Information](#)

Cache	Graphics	Max TDP
6 MB	No	80
Spec #	Min. BIOS	AA Rev(s)
SLANJ	1148	D94664-402
SLANJ	1148	D94664-403
SLANJ	1148	D94664-500

Add-in graphics card required

## Intel® Core™2 Extreme Desktop QX9775 | Frequency: 3.20 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 156
Spec # SLANY SLANY	Min. BIOS 1148 1148	AA Rev(s) D94664-402 D94664-500

Add-in graphics card required

## Quad-Core Intel® Xeon® E5472 | Frequency: 3.00 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec # SLANR SLANR SLANR SLANR SLANR	Min. BIOS 1148 1148 1148 1148 1148	AA Rev(s) D94664-402 D94664-403 D94664-500 D94664-501 D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® E5462 | Frequency: 2.80 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec # SLANT SLANT SLANT SLANT SLANT	Min. BIOS 1148 1148 1148 1148 1148	AA Rev(s) D94664-402 D94664-403 D94664-500 D94664-501 D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® E5450 | Frequency: 3.00 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec #	Min. BIOS	AA Rev(s)
SLANQ	1148	D94664-402
SLANQ	1148	D94664-403
SLANQ	1148	D94664-500
SLANQ	1148	D94664-501
SLANQ	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® E5440 | Frequency: 2.83 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec #	Min. BIOS	AA Rev(s)
SLANS	1148	D94664-402
SLANS	1148	D94664-403
SLANS	1148	D94664-500
SLANS	1148	D94664-501
SLANS	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® E5430 | Frequency: 2.66 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec #	Min. BIOS	AA Rev(s)
SLANU	1148	D94664-402
SLANU	1148	D94664-403
SLANU	1148	D94664-500
SLANU	1148	D94664-501
SLANU	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® E5420 | Frequency: 2.50 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec #	Min. BIOS	AA Rev(s)
SLANV	1148	D94664-402
SLANV	1148	D94664-403
SLANV	1148	D94664-500
SLANV	1148	D94664-501
SLANV	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® E5410 | Frequency: 2.33 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec #	Min. BIOS	AA Rev(s)
SLANW	1148	D94664-402
SLANW	1148	D94664-403
SLANW	1148	D94664-500
SLANW	1148	D94664-501
SLANW	1148	D94664-502

Add-in graphics card required

## Quad-Core Intel® Xeon® E5405 | Frequency: 2.00 GHz

[More Information](#)

Cache 12 MB	Graphics No	Max TDP 80
Spec #	Min. BIOS	AA Rev(s)
SLAP2	1148	D94664-402
SLAP2	1148	D94664-403
SLAP2	1148	D94664-500
SLAP2	1148	D94664-501
SLAP2	1148	D94664-502

Add-in graphics card required

# Dual-Core Intel® Xeon® E5205 | Frequency: 1.86 GHz

[More Information](#)

Cache  
6 MB

Graphics  
No

Max TDP  
65

Spec #  
SLANG  
SLANG  
SLANG  
SLANG  
SLANG

Min. BIOS

AA Rev(s)  
D94664-402  
D94664-403  
D94664-500  
D94664-501  
D94664-502

Add-in graphics card required