

# Intel® Server Board X38ML Memory List Test Report Summary

**Notice:** *This document will be discontinued in March 2009.*

*Please refer to the Sever Configuration tool for a complete list of tested hard drives at:  
<http://serverconfigurator.intel.com/default.aspx>*



Revision 12.0  
February 2009

Revision History		
Date	Rev	Modifications
Dec/07	1.0	Initial Release
Jan/08	2.0	Additional memory parts added (in shaded area).
Mar/08	3.0	Additional memory parts added (in shaded area).
Apr/08	4.0	Additional memory parts added (in shaded area).
Apr/08	5.0	Additional memory parts added (in shaded area).
May/08	6.0	Additional memory parts added (in shaded area).
June/08	7.0	Additional memory parts added (in shaded area).
Oct/08	8.0	Additional memory parts added (in shaded area).
Nov/08	9.0	Additional memory parts added (in shaded area).
Dec/08	10.0	Additional memory parts added (in shaded area).
Feb/09	11.0	Additional memory parts added (in shaded area).
Feb/09	12.0	<p>Additional memory parts added (in shaded area).</p> <p><b>Note:</b> Supported adapters, peripherals, hard drives and memory have been added for each Intel® Server product in the Server Configurator Tool. This document will be discontinued in March 2009. Please refer to the Sever Configuration tool for a complete list of tested memory at: <a href="http://serverconfigurator.intel.com/default.aspx">http://serverconfigurator.intel.com/default.aspx</a></p>

INTEL DISCLAIMS ALL LIABILITY FOR THESE DEVICES, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS RELATING TO THESE DEVICES OR THE IMPLEMENTATION OF INFORMATION IN THIS DOCUMENT. INTEL DOES NOT WARRANT OR REPRESENT THAT SUCH DEVICES OR IMPLEMENTATION WILL NOT INFRINGE SUCH RIGHTS. INTEL IS NOT OBLIGATED TO PROVIDE ANY SUPPORT, INSTALLATION, OR OTHER ASSISTANCE WITH REGARD TO THESE DEVICES.

THE INTEL PRODUCT REFERRED TO IN THIS DOCUMENT IS INTENDED FOR STANDARD COMMERCIAL USE ONLY. CUSTOMERS ARE SOLELY RESPONSIBLE FOR ASSESSING THE SUITABILITY OF THE PRODUCT AND/OR DEVICES FOR USE IN PARTICULAR APPLICATIONS. THE REFERENCED INTEL PRODUCT IS NOT INTENDED FOR USE IN CRITICAL CONTROL OR SAFETY SYSTEMS OR IN NUCLEAR FACILITY APPLICATIONS.

Information in this document is provided in connection with Intel products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by the sale of Intel products. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life saving, or life sustaining applications. Intel retains the right to make changes to its test specifications and memory list at any time, without notice.

The hardware vendor remains solely responsible for the design, sale and functionality of its product, including any liability arising from product infringement or product warranty. Only approved software drivers and accessories that are recommended for the revision number of the boards and system being operated should be used with Intel products. Please note that, as a result of warranty repairs or replacements, alternate software and firmware versions may be required for proper operation of the equipment.

The Intel® Server Board X38ML may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Copyright © Intel Corporation 2008-2009

\* Other brands and names are the property of their respective owners.

---

**Please Note:** DIMM devices with gold contacts should NOT be placed into DIMM sockets with tin-lead contacts or vice-versa. Mixing dissimilar metal contact types has been shown to result in unreliable memory operation. Intel recommends similar manufacturer and similar speeds in each bank on the memory module. Mixing of dissimilar memory manufacturer and similar speeds in each bank on the memory module is NOT recommended.

---

# Table of Contents

<b>OVERVIEW OF MEMORY TESTING.....</b>	<b>5</b>
UNBUFFERED, ECC, DDR2-667 DIMM MODULES 512 MB SIZES (64Mx72) .....	8
UNBUFFERED, ECC, DDR2-800 DIMM MODULES 512 MB SIZES (64Mx72) .....	8
UNBUFFERED, ECC, DDR2-667 DIMM MODULES 1 GB SIZES (128Mx72).....	9
UNBUFFERED, ECC, DDR2-800 DIMM MODULES 1 GB SIZES (128Mx72).....	9
UNBUFFERED, NON-ECC, DDR2-667 DIMM MODULES 1 GB SIZES (128Mx72) .....	10
UNBUFFERED, NON-ECC, DDR2-800 DIMM MODULES 1 GB SIZES (128Mx72) .....	10
UNBUFFERED, ECC, DDR2-667 DIMM MODULES 2 GB SIZES (256Mx72).....	11
UNBUFFERED, ECC, DDR2-800 DIMM MODULES 2 GB SIZES (256Mx72).....	11
UNBUFFERED, NON-ECC, DDR2-800 DIMM MODULES 2 GB SIZES (256Mx72).....	12
<b>SALES INFORMATION.....</b>	<b>13</b>
<b><u>CMTL* (COMPUTER MEMORY TEST LABS) .....</u></b>	<b>15</b>

## Overview of Memory Testing

The following procedure is used to test memory modules for use in the Intel® Server Board X38ML. Memory is a vital subsystem in a platform. Intel Corporation requires strict guidelines to be met before a memory vendor and part is put onto the qualified memory list. Each Intel Server Board product has a separate qualified memory list.

Memory qualification for Intel's Server Board products is performed by Intel's Memory Validation Laboratory (MVL), and by an independent external test laboratory, Computer Memory Test Lab (CMTL)<sup>1</sup>. CMTL is a leading memory testing organization responsible for testing a broad range of memory products. Memory devices tested by Intel's MVL or CMTL must undergo rigorous tests to ensure that the product will perform the intended server functions.

Intel®'s Server and Workstation Board qualified memory lists categorize memory modules as Advanced Tested. The Advanced Testing process involves a paper qualification, a standard voltage and room temperature functional test, and a voltage and temperature margin functional test. A paper qualification is a review of critical timings, electrical characteristics, timing requirements, environmental requirements, and packaging requirements in order to see if the memory meets Intel's memory specifications. The standard voltage and room temperature test involves testing the memory module on the particular Intel board for which it is being qualified with test software operating under Microsoft® Windows Server 2003® Enterprise Edition for no less than 24 hours. The voltage and temperature margin testing involves testing the memory module on the particular Intel board for which it is being qualified with various test software and operating systems for 48-72 hours under various voltage and temperature margin conditions. Memory modules that have completed Advanced Testing are known to be compatible with the product on which they were tested, and with the test software and operating system that was utilized during the test procedure.

For information regarding the testing procedure required to reach each phase, please contact your Intel Representative.

---

<sup>1</sup> CMTL is an independent memory testing organization responsible for testing a broad range of memory products. Receiving a "PASS" after being tested by CMTL, means that a product functions correctly and consumers can use it to perform the intended server functions. In order to pass these stringent standards, memory products must maintain the highest manufacturing procedures and pass an exacting battery of tests. Testing is performed with equipment and a procedure as defined by Intel's various functional testing levels.

CMTL contact:

Office: (949) 716-8690  
Fax (949) 716-8691

Computer Memory Test Lab (CMTL)  
24 Hammond Suite F  
Irvine, CA 92618  
<http://www.cmtlabs.com/>

## Qualified Memory for the Intel® Server Board X38ML

The memory module on the Intel® Server Board X38ML has 4 DIMM sockets, which can hold up to 8 GB of Unbuffered ECC and non-ECC DDR2-667 or DDR2-800 memory using four 72-bit DIMM modules. The following memory features are supported:

- DDR2-667 and DDR2-800 Unbuffered ECC and non-ECC compatible 1.8V modules (in compliance with the DDR JEDEC DIMM Specification).
- DIMMs with capacity of 512 MB, 1 GB and 2 GB. Other DRAM sizes may function correctly but will not be validated.
- Minimum configuration is 512 MB using one 512 MB DIMM.
- Maximum configuration is 8 GB.

Below is a chart that lists the current supported memory types:

DDR2-667 Unbuffered SDRAM Module Matrix					
DIMM Capacity	DIMM Organization	SDRAM Density	SDRAM Organization	# SDRAM Devices/rows/Banks	# Address bits rows/Banks/column
512 MB	64M x 72	256Mbit	32M x 8	18/2/4	13/2/10
512 MB	64M x 72	512Mbit	64M x 8	9/1/4	14/2/10
1 GB	128M x 72	512Mbit	64M x 8	18/2/4	14/2/10
1 GB	128M x 72	1Gbit	128M x 8	9/1/8	14/3/10
2 GB	256M x 72	1Gbit	128M x 8	18/2/8	14/3/10
DDR2-800 Unbuffered SDRAM Module Matrix					
DIMM Capacity	DIMM Organization	SDRAM Density	SDRAM Organization	# SDRAM Devices/rows/Banks	# Address bits rows/Banks/column
512 MB	64M x 72	256Mbit	32M x 8	18/2/4	13/2/10
512 MB	64M x 72	512Mbit	64M x 8	9/1/4	14/2/10
1 GB	128M x 72	512Mbit	64M x 8	18/2/4	14/2/10
1 GB	128M x 72	1Gbit	128M x 8	9/1/8	14/3/10
2 GB	256M x 72	1Gbit	128M x 8	18/2/8	14/3/10

Memory features are detailed in the *Intel® Server Board X38ML Technical Product Specification* available on-line at: <http://support.intel.com/support/motherboards/server/X38ML/index.htm>

The following table lists DIMM devices known to be compatible with the Intel® Server Board X38ML. Intel recommends that Advanced Tested DIMMs be used to establish reliable system operation. DIMM devices not listed can be used; but, in the event of unreliable system operation, the DIMM devices should be replaced with functionally Advanced Tested DIMMs to determine whether the DIMM devices are causing the problem.

**Caution:** Third party memory vendors may use the same module part number with different DRAM vendors and die revisions. To insure proper system operation, verify that each DRAM vendor and die revision has been separately tested and qualified. Please notify CMTL if there is a discrepancy.

**Note:** This list is not intended be all-inclusive. It is provided as a convenience to Intel's general customer base, but Intel does not make any representations or warranties whatsoever regarding the quality, reliability, functionality, or compatibility of these memory modules.

***This list is subject to change without notice.***

**Intel® Server Board X38ML**  
**Unbuffered, ECC, DDR2-667 DIMM Modules**  
**512 MB Sizes (64Mx72)**

Manufacturer	Part Number	DRAM Part Number	DRAM Vendor	PCB Part Number	CAS Latency	DRAM Organization	Date
Micron	MT9HTF6472AY-667D4	7FD22 D9GMH	Micron		5	(64Mx8)*9	11/07

**Unbuffered, ECC, DDR2-800 DIMM Modules**  
**512 MB Sizes (64Mx72)**

Manufacturer	Part Number	DRAM Part Number	DRAM Vendor	PCB Part Number	CAS Latency	DRAM Organization	Date
Micron	MT9HTF6472AY-80ED4		Micron		5	(64Mx8)*9	11/07
Samsung	M391T6553EZ3-CE7	K4T51083QE-ZCE7	Samsung		5	(64Mx8)*9	11/07
Qimonda	HYS72T64000HU-25F-B2	HYB18T512800B2F25F	Qimonda		5	(64Mx8)*9	11/07
Hynix	HYMP564U72CP8-S6	HY5PS12821C FP-S6	Hynix		6	(64Mx8)*9	11/07
Dataram	DTM63359B	HY5PS12821CFP-S5 rev C	Hynix	40083A rev A	5	(64Mx8)*9	12/21/07
Ventura Technology Group	D2-52DD63SV-555	K4T51083QC-ZCE7 rev C	Samsung	D2U72F na	5	(64Mx8)*9	1/7/08
Dataram	DTM63390A	HYB18T1G160C2F-25F rev C2	Qimonda	40104A rev A	5	64M x 16	11/14/09
Dataram	DTM63390A	HYB18T1G160C2F-25F rev C2	Qimonda	40104A rev A	5	64M x 16	11/14/09

(+) This vendor is part of the CMTL Certification program. This means this part has/will been tested across all compatible Intel Server Boards. For further information contact CMTL @ <http://cmtlabs.com/>

**Caution:** Some modules on this list may contain “stacked” DRAM parts. These parts may have thermal & physical limitations in some chassis configurations. It is advised to verify that your chassis configuration will support “stacked” parts before purchase.



## *Intel® Server Board X38ML*

### **Unbuffered, ECC, DDR2-667 DIMM Modules 1 GB Sizes (128Mx72)**

Manufacturer	Part Number	DRAM Part Number	DRAM Vendor	PCB Part Number	CAS Latency	DRAM Organization	Date
Qimonda	HYS72T128020EU-3S-B2	HYB18T512800B2F3S	Qimonda		5	(64Mx8)*18	11/07
ATP Electronics	AJ28K72F8BJE6S	K4T1G084QD-ZCE6 rev D	Samsung	D2U72F na	5	(128Mx8)*9	1/4/08
Hynix	HYMP512U72CP8-Y5	HY5PS12821CFP-Y5	Hynix		5	(64Mx8)*18	1/24/08
Samsung	M391T2953EZ3-CE6	K4T51083QE-ZCE6	Samsung		5	(64Mx8)*18	1/24/08
STEC	INT72Q8M128M8M-A03GYU	HYB18T512800BF3S rev B	Qimonda	D2U72G na	5	(64Mx8)*18	1/25/08
Samsung	M391T2863QZ3-CE6	Kr4T1G084QQ-HCF7	Samsung		5	(128Mx8)*9	3/18/08
Smart Modular Technologies	SG1287UD212852HC	HY5PS1G831CFP-Y5 rev C	Hynix	PG54G240 NUBUB1RF rev A	5	(128Mx8)*9	4/11/08
Hynix	HYMP112U72CP8-Y5	HY5PS1G831CFP-Y5	Hynix		5	(128Mx8)*9	6/18/08
STEC	INT72Q8M128M8M-A03GYU	HYB18T512800B2F-3S rev B2	Qimonda	D2U72G	5	64M x 8	09/30/08

### **Unbuffered, ECC, DDR2-800 DIMM Modules 1 GB Sizes (128Mx72)**

Manufacturer	Part Number	DRAM Part Number	DRAM Vendor	PCB Part Number	CAS Latency	DRAM Organization	Date
Micron	M18HTF12872AY-80ED4		Micron		5	(64Mx8)*18	11/07
Samsung	M391T2953EZ3-CE7	K4T51083QE-ZCE7	Samsung		5	(64Mx8)*18	11/07
Qimonda	HYS72T128020EU-25F-B2	HYB18T512800B2F25F	Qimonda		5	(64Mx8)*18	11/07
Hynix	HYMP512U72CP8-S6 A	HY5PS12821C FP-S6	Hynix		6	(64Mx8)*18	11/07
Dataram	DTM63358B	HY5PS12821CFP-S5 rev C	Hynix	40082A rev A	5	(64Mx8)*18	12/19/07
Ventura Technology Group	D2-54DD64SV-555	K4T51083QC-ZCE7 rev C	Samsung	D2U72G na	5	(64Mx8)*18	1/9/08
Apacer	78.01GAE.42D	E1108ACBG-8E-E rev C	Elpida	48.16193.0 9D rev D	5	(128Mx8)*9	1/14/08
Apacer	78.01G9Q.423	E5108AJBG-8E-E rev J	Elpida	48.18193.0 93 rev 3	5	(64Mx8)*18	1/23/08
Samsung	M391T2863QZ3-CF7	K4T1G084QQ-HCE6	Samsung		6	(128Mx8)*9	3/18/08
Kingston	KVR800D2E5/1GI	E5108AJBG-8E-E	Elpida		5	(64Mx8)*18	3/29/08
Kingston	KVR800D2E5/1GI	NT5TU64M8BE-25C	Nanya		5	(64Mx8)*18	3/26/08
Hynix	HYMP112U72CP8-S6	HY5PS1G831CFP-S6	Hynix		6	(128Mx8)*9	6/18/08
Kingston	KVR800D2E5/1GI	E1108ACBG-8E-E rev C	Elpida	2025320-0F1.A00 rev A	5	128M x 8	10/27/08
Dataram	DTM63393A	HYB18T1G800C2F-25F rev C2	Qimonda	40083A rev A	5	128M x 8	12/11/08

(+) This vendor is part of the CMTL Certification program. This means this part has/will be tested across all compatible Intel Server Boards. For further information contact CMTL @ <http://cmtlabs.com/>

**Caution:** Some modules on this list may contain "stacked" DRAM parts. These parts may have thermal & physical limitations in some chassis configurations. It is advised to verify that your chassis configuration will support "stacked" parts before purchase.

## **Intel® Server Board X38ML**

### **Unbuffered, Non-ECC, DDR2-667 DIMM Modules 1 GB Sizes (128Mx72)**

<b>Manufacturer</b>	<b>Part Number</b>	<b>DRAM Part Number</b>	<b>DRAM Vendor</b>	<b>PCB Part Number</b>	<b>CAS Latency</b>	<b>DRAM Organization</b>	<b>Date</b>
Buffalo	D2U667C-1GEJJ	E5108AJBG-6E-E rev J	Elpida	2DUE28F-AA na	5	(64Mx8)*18	1/29/08

### **Unbuffered, Non-ECC, DDR2-800 DIMM Modules 1 GB Sizes (128Mx72)**

<b>Manufacturer</b>	<b>Part Number</b>	<b>DRAM Part Number</b>	<b>DRAM Vendor</b>	<b>PCB Part Number</b>	<b>CAS Latency</b>	<b>DRAM Organization</b>	<b>Date</b>
ATP Electronics	AJ28K64E8BHE7S	K4T51083QE-ZCE7 rev E	Samsung	SJ240E08K1 na	5	(64Mx8)*18	1/16/08
Buffalo	D2U800CX-S1GECJ	E1108ACBG-8E-E rev C	Elpida	2D286NF3-AB	5	128M x 8	01/19/09

(+) This vendor is part of the CMTL Certification program. This means this part has/will been tested across all compatible Intel Server Boards. For further information contact CMTL @ <http://cmtlabs.com/>

**Caution:** Some modules on this list may contain "stacked" DRAM parts. These parts may have thermal & physical limitations in some chassis configurations. It is advised to verify that your chassis configuration will support "stacked" parts before purchase.

# Intel® Server Board X38ML

## Unbuffered, ECC, DDR2-667 DIMM Modules 2 GB Sizes (256Mx72)

Manufacturer	Part Number	DRAM Part Number	DRAM Vendor	PCB Part Number	CAS Latency	DRAM Organization	Date
Micron	MT18HTF25672AY-667E1	7EEII D9HNL	Micron		5	(128Mx8)*18	11/07
Qimonda	HYS72T256020HU-3S-B	HYB18T1G800AF-3S	Qimonda		5	(128Mx8)*18	11/07
Qimonda	HYS72T256020EU-3S-B	HYB18T1G800BF-3S-B	Qimonda		5	(128Mx8)*18	1/08
Hynix	HYMP125U72CP8-Y5	HY5PS1G831CFP-Y5	Hynix		5	(128Mx8)*18	1/08
ATP Electronics	AJ56K72G8BJE6M	MT47H128M8HQ-3 rev E	Micron	SJ240G08K 1 na	5	(128Mx8)*18	2/08
ATP Electronics	AJ56K72G8BJE6S	K4T1G084QD-ZCE6 rev D	Samsung	SJ240G08K 1 na	5	(128Mx8)*18	1/08
STEC	INT72Q8W256M8M-A03GYU	MT47H128M8HQ-3 rev E	Micron	D2U72G na	5	(128Mx8)*18	1/08
TRS	TRS30321X	E1108AB-6E-E rev B	Elpida	M0540LA1 rev 1	5	(128Mx8)*18	3/08
Samsung	M391T5663QZ3-CE6	Kr4T1G084QQ-HCF7	Samsung		5	(128Mx8)*18	3/08
Kingston	KVR667D2E5/2GI	E1108ACSE-6E-E	Elpida		5	(128Mx8)*18	4/10/08

## Unbuffered, ECC, DDR2-800 DIMM Modules 2 GB Sizes (256Mx72)

Manufacturer	Part Number	DRAM Part Number	DRAM Vendor	PCB Part Number	CAS Latency	DRAM Organization	Date
Micron	MT18HTF25672AY-80EE1	7HEII D9HNQ	Micron		5	(128Mx8)*18	11/07
Samsung	M391T5663DZ3-CE7	K4T51083QE-ZCE6	Samsung		5	(128Mx8)*18	11/07
Smart Modular Technologies	SG2567UDR212851ME	MT47H128M8HQ-25E rev E	Micron	PG58G240 NUBUB1RG rev A	5	(128Mx8)*18	12/07
ATP Electronics	AJ56K72G8BJE7M	MT47H128M8HQ-25E rev E	Micron	SJ240G08K 1 na	5	(128Mx8)*18	1/08
Apacer	78.A1GAE.423	E1108ACBG-8E-E rev C	Elpida	48.18193.09 3 rev 3	5	(128Mx8)*18	1/08
Samsung	M391T5663QZ3-CF7	K4T1G084QQ-HCE6	Samsung		6	(128Mx8)*18	3/08
Kingston	KVR800D2E5/2GI	HY5PS1G831CFP-S5	Hynix		5	(128Mx8)*18	4/4/08
Hynix	HYMP125U72CP8-S6	HY5PS1G831CFP-S6	Hynix		6	(128Mx8)*18	6/18/08
Kingston	KVR800D2E5/2GI	E1108ACBG-8E-E	Elpida		5	(128Mx8)*18	6/5/08

(+) This vendor is part of the CMTL Certification program. This means this part has/will been tested across all compatible Intel Server Boards. For further information contact CMTL @ <http://cmtlabs.com/>

**Caution:** Some modules on this list may contain "stacked" DRAM parts. These parts may have thermal & physical limitations in some chassis configurations. It is advised to verify that your chassis configuration will support "stacked" parts before purchase.

## ***Intel® Server Board X38ML***

***Unbuffered, non-ECC, DDR2-800 DIMM Modules  
2 GB Sizes (256Mx72)***

<b>Manufacturer</b>	<b>Part Number</b>	<b>DRAM Part Number</b>	<b>DRAM Vendor</b>	<b>PCB Part Number</b>	<b>CAS Latency</b>	<b>DRAM Organization</b>	<b>Date</b>
Buffalo	D2U800CX-2GECJ	E1108ACBG-8E-E rev C	Elpida	2D286NF3-AB	5	128M x 8	01/22/09

(+) This vendor is part of the CMTL Certification program. This means this part has/will been tested across all compatible Intel Server Boards. For further information contact CMTL @ <http://cmtlabs.com/>

**Caution:** Some modules on this list may contain “stacked” DRAM parts. These parts may have thermal & physical limitations in some chassis configurations. It is advised to verify that your chassis configuration will support “stacked” parts before purchase.

## Sales Information

Vendor Name	Web URL	Vendor Direct Sales Info
ATP Electronics	<a href="http://www.atpusa.com/">http://www.atpusa.com/</a>	Tel (1) 408-732-5000, ext 5858 Fax 408-732-5893 <a href="mailto:sales@atpusa.com">sales@atpusa.com</a>
ATP Electronics -- Taiwan Inc.	<a href="http://www.atpusa.com/">http://www.atpusa.com/</a>	Tel 011-886-2-2659-6368 Fax 886-2-2659-4982
Avant Technology	<a href="http://www.avanttechnology.com">http://www.avanttechnology.com</a>	Brad Scoggins Phone: (512)491-7411 Fax: (512)491-7412 <a href="mailto:brads@avanttechnology.com">brads@avanttechnology.com</a>
Aved Memory Products	<a href="http://www.avedmemory.com/">http://www.avedmemory.com/</a>	
Buffalo Technology	<a href="http://www.buffalotech.com/">http://www.buffalotech.com/</a>	(800) 967-0959 <a href="mailto:memory@buffalotech.com">memory@buffalotech.com</a>
Centon Electronics	<a href="http://www.centon.com">http://www.centon.com</a>	Tel: 949-855-9111 Fax: 949-855-6035
Corsair	<a href="http://www.corsairmicro.com/">http://www.corsairmicro.com/</a>	Tel: 510-657-8747 Fax: 510-657-8748
Crucial	<a href="http://www.crucial.com/intel">http://www.crucial.com/intel</a>	Toll-free: 888-363-4167 (US & Canada only) Tel: 208-363-5790 Fax: 208-363-5560 <a href="mailto:crucial.sales@micron.com">crucial.sales@micron.com</a>
Dane-Elec	<a href="http://www.dane-memory.com/">http://www.dane-memory.com/</a>	Michal Hassan @ (949)450-2941 or email @ <a href="mailto:Michal@Dane-memory.com">Michal@Dane-memory.com</a>
Dataram	<a href="http://www.dataram.com/">http://www.dataram.com/</a>	Paul Henke, 800-328-2726 x2239 in USA <a href="mailto:phenke@dataram.com">phenke@dataram.com</a> Peter Jauss, +49-69-680-9070 in EMEA <a href="mailto:pjauss@dataram.com">pjauss@dataram.com</a>
GoldenRAM	<a href="http://www.goldenram.com">http://www.goldenram.com</a>	Jason M. Barrette @ 800-222-861 x7546 <a href="mailto:jasonb@goldenram.com">jasonb@goldenram.com</a> or Michael E. Meyer @800-222-8861 x7512 <a href="mailto:michaelm@goldenram.com">michaelm@goldenram.com</a>
Hitachi	<a href="http://semiconductor.hitachi.com/pointer/">http://semiconductor.hitachi.com/pointer/</a>	
Hyundai/Hynix Semiconductor	<a href="http://www.hea.com/">http://www.hea.com/</a>	
Infineon	<a href="http://www.infineon.com/business/distribut/index.htm">http://www.infineon.com/business/distribut/index.htm</a>	
ITAUCOM	<a href="http://www.itaucum.com.br">http://www.itaucum.com.br</a>	
JITCO CO LTD	<a href="http://www.jitco.net/">http://www.jitco.net/</a>	Seong Jeon Tel: 82-32-817-9740 <a href="mailto:s.jeon@jitco.net">s.jeon@jitco.net</a>
Kingston	<a href="http://www.kingston.com">http://www.kingston.com</a>	US.- Call (877) 435-8726 Asia – Call 886-3-564-1539 Europe – Call +44-1932-755205
Legacy Electronics Inc.	<a href="http://www.legacyelectronics.com">http://www.legacyelectronics.com</a>	U.S. Contact: Keri Albers 888 466 3853 ext. 307 European Contact: 49 89 370 664 11
Legend	<a href="http://www.legend.com.au">http://www.legend.com.au</a>	
Micron	<a href="http://www.micron.com">http://www.micron.com</a>	
MSC Vertriebs GmbH	<a href="http://www.msc-ge.com">http://www.msc-ge.com</a>	William Perrigo 49-7249-910-417 Fax: 49-7249-910-229 <a href="mailto:wpe@msc-ge.com">wpe@msc-ge.com</a>
Netlist, Inc	<a href="http://www.netlistinc.com">http://www.netlistinc.com</a>	Christopher Lopes 949.435.0025 tel 949.435.0031 fax <a href="mailto:sales@netlistinc.com">sales@netlistinc.com</a>

Vendor Name	Web URL	Vendor Direct Sales Info
<b>Peripheral Enhancements</b>	<a href="http://www.peripheral.com/">http://www.peripheral.com/</a>	
<b>PNY</b>	<a href="http://www.pny.com/internet_explorer/LPB.HTML">http://www.pny.com/internet_explorer/LPB.HTML</a>	
<b>Samsung</b>	<a href="http://www.korea.samsungsemi.com/locate/buy/list_na.html">http://www.korea.samsungsemi.com/locate/buy/list_na.html</a>	For US customers go to: <a href="http://www.mymemorystore.com/">http://www.mymemorystore.com/</a>
<b>Silicon Tech</b>	<a href="http://www.silicontech.com/contact/salescontacts.shtml">http://www.silicontech.com/contact/salescontacts.shtml</a>	
<b>Simple Tech</b>	<a href="http://www.simpletech.com">http://www.simpletech.com</a>	Ron Darwish @ (949) 260-8230 or email @ <a href="mailto:Rdarwish@Simpletech.com">Rdarwish@Simpletech.com</a>
<b>SMART Modular Technologies</b>	<a href="http://www.smartm.com/channel/hpc/">www.smartm.com/channel/hpc/</a>	Gene F. Patino Tel: 949 439-6167 <a href="mailto:gene.patino@smartm.com">gene.patino@smartm.com</a>
<b>TechnoLinc Corporation</b>	<a href="http://www.technolinc.com">http://www.technolinc.com</a>	David Curtis 510-445-7400 <a href="mailto:davide@technolinc.com">davide@technolinc.com</a>
<b>TRS* Tele-Radio-Space GmbH</b>	<a href="http://www.certified-memory.com">http://www.certified-memory.com</a> <a href="http://www.certified-memory.de">http://www.certified-memory.de</a>	Vender Direct Sales Info: Andreas Gruendl Tel: +49.89.945532-34 Fax: +49.89.945532-41 <a href="mailto:Andreas.gruendl@trs-eu.com">Andreas.gruendl@trs-eu.com</a>
<b>Unigen</b>	<a href="http://www.unigen.com">http://www.unigen.com</a>	
<b>Ventura Technology Inc</b>	<a href="http://www.venturatech.com">http://www.venturatech.com</a>	Sam Lewis 760 724-8700 ext. 103
<b>Viking InterWorks</b>	<a href="http://www.vikinginterworks.com">http://www.vikinginterworks.com</a>	Adrian Proctor Tel: 949-643-7255 <a href="mailto:adrian.proctor@sanmina-sci.com">adrian.proctor@sanmina-sci.com</a>
<b>Virtium Technology Inc</b>	<a href="http://www.virtium.com">http://www.virtium.com</a>	Tod Skelton @ (949) 460-0020 ext. 146 or email @ <a href="mailto:tod.skelton@virtium.com">tod.skelton@virtium.com</a>
<b>Wintec Industries</b>	<a href="http://www.wintecindustries.com">http://www.wintecindustries.com</a>	Tel 510-360-6300 Fax 510-770-9338

### **CMTL\* (Computer Memory Test Labs)**

CMTL is a privately owned and operated memory testing organization responsible for testing a broad range of memory products. Memory devices tested by CMTL must undergo a rigorous battery of tests to ensure that the product will perform the intended server functions. Memory capability is a major factor your customers consider. CMTL has the ability to test and certify memory on Intel-based server platforms. The list of memory modules, which have undergone testing through the CMTL facility, should be referenced when considering modules for integration into this Intel server product. Stringent standards with regard to manufacturing procedures and quality must be met to pass the exacting tests required for qualification through the independent testing facility. Testing is performed by CMTL with Intel server products and test procedures defined by Intel's Memory Validation Lab. Intel routinely audits the CMTL facility to ensure all procedures, process handling, and testing methodologies are met.

#### **IMPORTANT NOTE**

DIMM devices with gold contacts should NOT be placed into DIMM sockets with tin-lead contacts or vice-versa. Mixing dissimilar metal contact types has been shown to result in unreliable memory operation. Intel recommends similar manufacturer and similar speeds in each bank on the memory module. Mixing of dissimilar memory manufacturer devices or dissimilar memory device speeds is not recommended. This document contains information which is the proprietary property of Intel Corporation. Nothing in this document constitutes a guaranty, warranty, or license, express or implied. Intel has tested the following DIMMs for minimum electrical and functional compatibility with boxed processors. This listing is not intended to be all inclusive; it only represents the DIMMs Intel or CMTL has tested. Users of this list are reminded to check with the DIMM manufacturer or Distributor to ensure that a particular DIMM model is adequate for the intended purpose on the boxed processor baseboard. Intel provides no indemnities for and expressly disclaims all liabilities for any and all such guaranties, representations, and warranties (oral or written) whether express or implied, related to DIMMs in an Intel® Server Board product, including without limitation to: fitness for a particular purpose; merchantability; noninfringement of intellectual property or other rights of any third party or of Intel. The reader is advised that third parties may have intellectual property rights which may be relevant to this document and the technologies discussed herein, and is advised to seek the advice of competent legal counsel, without obligation of Intel. Intel retains the right to make changes to this document at any time, without notice. Intel makes no warranty or representation with respect to the use of this document or reliance by the reader upon its contents, and assumes no responsibility for any errors which may appear in the document nor does it make a commitment to update the information contained herein.

Product and corporate names listed in this document may be trademarks of their respective companies.